



Typical Inspection Data:

Density @ 20°C	0.848 g/cm ³
Viscosity @ 100°C	12.2 cSt
Viscosity @ 40°C	73 cSt
Viscosity Index	165
Viscosity CCS @ -30°C	6000 cP
T.B.N.	8.2 mg KOH/g
Sulphated Ash Mass	0.7%
Zinc	0.09%
Calcium	0.07%
Phosphorus	0.07%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

Eco-R 5W-30

Fully Synthetic

Recommended by Comma for applications requiring:

ACEA C3; Renault RN-17

Product Features:

- Fully synthetic, high performance 5W-30 engine oil. Suitable for modern petrol and diesel vehicles.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 16-09-2022