



Typical Inspection Data:

| | |
|-------------------|-------------------------|
| Density @ 20°C | 0.833 g/cm ³ |
| Viscosity @ 40°C | 26.2 cSt |
| Viscosity @ 100°C | 6.10 cSt |
| Colour | Straw |
| Flash Point | 220°C |
| Pour point | -69°C |
| Viscosity Index | 194 |
| Phosphorus | 0.02% |

EXT Fluid

Central Hydraulic Fluid

Recommended by Comma for applications requiring:

GM 89021185 / GM 89021186, GM 1052884 / GM 993294, GM 19329450 / GM 19329451, GM 1940707, GM 89020661; Hyundai / Kia PSF-3, PSF-4; Chrysler MS 5931; Fiat 9.55550-AG1, AG2, AG3 ISO VG 22, AV4; Texaco Cold Climate Power Steering Fluid; Saab P/N 45 30 09 800; Special Power Steering Fluid, Dia-Queen PSF; Pentosin CHF 7.1; Special Power Steering Fluid, Toyota Type EH; Nissan PSF-II

Product Features:

- EXT Fluid is a special synthetic based hydraulic fluid suitable for central hydraulic systems, power steering and suspension level control systems. Also suitable for certain stability and traction control systems, hydrostatically driven fans, generators and air conditioning units, control of convertible car top covers and central locking systems.

Directions for use:

- Always follow the vehicle manufacturer's recommendations when adding EXT Fluid.
- Check vehicle handbook if in doubt.
- Keep fluid clean.
- Caution: Store only in its original container.
- Keep container clean and tightly closed.
- Do not refill container or use for other liquids.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 04-04-2019